



ASSEMBLY INSTRUCTIONS

Illustration A:



To assemble safety cables:

1. Join fixture safety cables with safety cable from ceiling.
2. Wrap both safety cable around the lock nut (a).
3. Insert clip (b) into both holes on lock nut (a), secure with nuts (c).
4. Push the lock nut into outlet box.



Club Large Hexagonal Flush Mount

Item # CHC4126

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING * SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.**

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT, DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

1. Open the door (G) by loosening the locking pins (H).
2. To install glass panel (L) provided to front frame (G), make sure metal tabs (J) are flipped against the opening of the frame. Place glass panel (L) to front frame and secure glass panel (L) by bending back metal tabs (J) towards the glass panel. Install rest of the six glass panels (K) into side frames and secure with the metal tabs on the frame.
3. Attach the top hook on the candelabra assembly (I) to the loop (M).
4. Remove mounting plate (B) from lantern base (E) by removing base screws (D) and set aside.
5. Place mounting plate (B) on the ceiling outlet box, use mounting plate (B) as a template, mark center points for four mounting holes on the mounting plate (B). Remove mounting plate (B).
6. Drill small holes on the marked location, the holes should be big enough to accommodate with plastic anchors (A). Push plastic anchors (A) into the holes.
7. Connect the safety steel wire from the fixture to the safety cable from ceiling with lock nut. (As shown in illustration A)
8. Connect the hot wire from the fixture (with words on surface) to the hot junction box wire from the outlet box (usually BLACK). Fasten them together with a plastic wire connector provided and wrap connection with electrical tape.
9. Repeat this procedure for the neutral wire from the light fixture (without words on surface) to the wire from the outlet box (usually WHITE).
10. Connect the ground wire from the light fixture (bare copper) to the ground wire from the outlet box.

