

## ASSEMBLY INSTRUCTIONS

## Halo Petite Flush Mount

Item # KS5553

**WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.**

**WARNING\*\*\*SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.**

**INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT. DO NOT INSTALL.**

**ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.**

**NOTE: CAREFULLY UNPACK EACH PIECE IN TOP LAYER OF PACKING PRIOR TO REMOVING. RETAIN ALL PACKING MATERIAL UNTIL INSPECTION AND INSTALLATION ARE FINAL.**

1. Carefully remove all parts from the box.
2. Remove the collar ring (E) from the center of the mounting plate (C).
3. Install the mounting plate (A) to junction box by secure with the mounting screws (B).
4. Feed the wires through the rods (G), collar ring (E), canopy (D) and rod (F).
5. Thread the rod (G) into the connector (H) then thread the tube (F) to the rod (G).
6. Hang the fixture swivel ball (L) to the center of the mounting plate (C).
7. Measure the wires then cut, be certain to leave enough to connect house wires.
8. Strip the insulation back on the two power supply wires about 5/8".
9. Connect the fixture ground wire to the house ground wire with the wire nut (E).  
IT IS IMPERATIVE THAT THIS FIXTURE BE GROUNDED.
10. Connect the fixture ribbed wire (no marking) to the house neutral wire with the wire nut (E).
11. Connect the fixture smooth wire (with marking) to the house hot wire with the wire nut (E).  
DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OTHERWISE SAFETY WILL BE COMPROMISED.
12. Tuck the wire connections neatly into the junction box.
13. Attach the canopy (D) to the ceiling and secure with the collar ring (E).
14. Insert light bulbs (not included) into sockets.
15. Loosen the check ring (K) then move up the glass cap (I).
16. Install glass shade (J) to plate (M) by turning glass at an angle and resting on top of plate.  
Slide down the cap (I) and secure with ring (K).  
DO NOT OVER-TIGHTEN OTHERWISE THE GLASS SHADE COULD BE DAMAGED.
17. Installation is complete, turn on power at fuse or circuit breaker.

