


ASSEMBLY INSTRUCTIONS




1/4 IPS threaded nipple pipe
(Not provided)

Ceiling Box

Cable lock nut

Safety cable



- TO assemble safety cables:
1. Join fixture safety cables with safety cable from ceiling.
 2. Wrap both safety cable around the cable lock nut.
 3. Insert screws into both holes on cable lock nut, secure screws with screwdriver.
 4. Push the cable lock nut into outlet box.

O (32 sets)

P (14 sets)

Bulb
(Not included)

Natalie Large Tiered Chandelier

Item # RL 5634

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING*SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION.**

INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT. DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

NOTE: CAREFULLY UNPACK EACH PIECE IN TOP LAYER OF PACKING PRIOR TO REMOVING. RETAIN ALL PACKING MATERIAL UNTIL INSPECTION AND INSTALLATION ARE FINAL.



1. Carefully remove all parts from the box.
2. Thread the center cluster (R) to the connector (Q).
3. Provide a 1/4" IPS pipe with one end securely mounted to a beam or a structural member. The other end should protrude through the center of the outlet box as shown.
4. Install the threaded nipple (B) into the support pipe and adjust overall length to allow the canopy ring to hold the canopy flush to the ceiling.
5. Put canopy (D) flush to the ceiling and secure with collar ring (E).
6. With the fixture desired height, shorten the chain (F) as needed using a pair of chain pliers.
7. Unscrew the screw (G) on the chain quick link (H), then attach the chain quick link (H) to the top ring (I). Secure the screw (G) to secure the fixture body.
8. Unscrew the screw (G) on the chain quick link (H), then attach the chain quick link (H) to the ceiling loop (C). Secure the screw (G).
9. Weave the power supply cord, ground wire and safety cable through the chain (F).
10. When you reach the canopy and ceiling loop, measure the wires then cut. Be certain to leave enough length to connect inside of the outlet box.
11. Strip the insulation back on the two power supply wires about 5/8".
12. Loosen the collar ring (E) and slip down the canopy (D) carefully.
13. Twist the power supply and ground wire together and push through the center hole of the ceiling loop (C).
14. Connect the fixture ground (bare) wire with the ground wire from the outlet box using wire nut (A). If your house does not have ground wire, then attach this wire to the green grounding screw inside of the outlet box.

IT IS IMPERATIVE THAT THIS FIXTURE BE GROUNDED.




RALPH LAUREN

ASSEMBLY INSTRUCTIONS



- TO assemble safety cables:
1. Join fixture safety cables with safety cable from ceiling.
 2. Wrap both safety cable around the cable lock nut.
 3. Insert screws into both holes on cable lock nut, secure screws with screwdriver.
 4. Push the cable lock nut into outlet box.



Natalie Large Tiered Chandelier

Item # RL 5634

WE RECOMMEND INSTALLATION OF THIS LIGHTING FIXTURE BE DONE BY A LICENSED ELECTRICIAN.

WARNING***SWITCH OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX/CIRCUIT BREAKER BEFORE INSTALLATION. INSPECT ITEM CAREFULLY BEFORE ATTEMPTING TO INSTALL. IF THERE IS ANY DAMAGE OR OBVIOUS DEFECT. DO NOT INSTALL.

ITEM MAY NOT BE RETURNED ONCE IT HAS BEEN INSTALLED.

NOTE: CAREFULLY UNPACK EACH PIECE IN TOP LAYER OF PACKING PRIOR TO REMOVING. RETAIN ALL PACKING MATERIAL UNTIL INSPECTION AND INSTALLATION ARE FINAL.

15. Connect the fixture Neutral wire (ribbed) with the neutral wire (White) from the outlet box using wire nut (A).
16. Connect the fixture Hot wire (smooth, marks with words) with the hot wire (Black) from the outlet box using wire nut (A).
DO NOT REVERSE THE HOT AND NEUTRAL CONNECTIONS OR SAFETY WILL BE COMPROMISED.
17. Tuck these wire connections neatly into the outlet box to secure.
18. Put canopy (D) flush to the ceiling and secure with collar ring (E).
19. Assembly the metal ring (L) to the metal ring (J) with rods (K).
20. Assembly the metal ring (N) to the metal ring (L) with rods (M).
21. Hang the metal drops (O) to the metal ring (J) and (N).
22. Hang the metal drops (P) to the metal ring (L).
23. Insert bulbs (not included) into the sockets.
24. Installation is complete, turn on power at fuse or circuit breaker.

***Clean with a dry, soft cloth only. Use no harsh abrasives or chemical agents.



RALPH LAUREN